





| Ref.     | A     | B  | C    | D  | E  | Charge de rupture (daN) | Poids (gr) |
|----------|-------|----|------|----|----|-------------------------|------------|
| OCS-0912 | 88    | 34 | 17,5 | 8  | 11 | 4900                    | 93         |
| OCS-0913 | 95    | 37 | 19   | 9  | 12 | 6250                    | 121        |
| OCS-0905 | 105,5 | 41 | 20,5 | 10 | 13 | 8000                    | 161        |
| OCS-0907 | 124   | 48 | 23,5 | 12 | 15 | 11000                   | 275        |
| OCS-0908 | 160   | 65 | 28   | 16 | 19 | 12500                   | 650        |

Matière : INOX 316L

| Révision     | Commentaire        |   |  |                       |                    |
|--------------|--------------------|---|---|-----------------------|--------------------|
| A            | Première diffusion |   |   |                       |                    |
| Dessiné par  | T.D                |  | Designation: Maillons [P]   |                       |                    |
| Vérifié par  | S.O.L              |  | FORMAT<br><b>A3</b>   | No. plan:<br>OCS-2035 | Date :<br>02/10/25 |
| Approuvé par | J.A                |  | Echelle: 1/0,75   | Poids: ---            | Feuille: 1/1       |